

# CoZIR<sup>®</sup>-LP<sup>2</sup>

**GSS**  
Gas Sensing Solutions

- **Ultra-Low-Power CO<sub>2</sub> sensor**
- **User-Defined power consumption**
- **Ideal for battery-powered operation**
- **Fit and forget, fully autonomous operation**
- **Long life, >15 years**



## About the CozIR-LP<sup>2</sup>

The CozIR<sup>®</sup>-LP<sup>2</sup> is an ultra-low power NDIR CO<sub>2</sub> sensor using state-of-the-art solid-state LED optical technology. The low-power LEDs are manufactured in-house, giving GSS complete control of the CO<sub>2</sub> sensor signal chain.

The CozIR<sup>®</sup>-LP<sup>2</sup> allows users to reduce power consumption whilst maintaining high CO<sub>2</sub> measurement accuracy. The sensor incorporates a number of power saving modes, capable of reducing active and quiescent current consumption to unrivalled low levels.

The CozIR<sup>®</sup>-LP<sup>2</sup> also features a built-in auto-calibration function that maintains CO<sub>2</sub> measurement accuracy over the lifetime of the product.

## Features

- Ultra-low power CO<sub>2</sub> sensor
- 30ppm (typ.) measurement accuracy
- Solid state LED optical technology
- UART or I<sup>2</sup>C control and data interface
- Built-in auto-calibration
- California Building Standards Code, Title 24 compliant

## Applications

- Indoor Air Quality (IAQ)
- IoT and Smart Technology wireless equipment
- Air Quality and HVAC Systems
- Building Management Systems (BMS)
- Demand-Controlled Ventilation (DCV) systems
- Transport
- In-Cabin Air Quality

# COZIR<sup>®</sup>-LP<sup>2</sup>

## Ordering Information

COZIR-LP2 - X

x	Measurement Range
2000	0-2000ppm
5000	0-5000ppm
1	0-1%

<https://www.gassensing.co.uk/product/cozir-lp2/>

**GSS**  
Gas Sensing Solutions



## CO<sub>2</sub> Sensor Specifications

Measurement Ranges	0-2000ppm, 0-5000ppm, 0- 10000ppm (0-1%)
Accuracy (typ.)	±(30ppm +3% of reading)
Time to 1st Reading	<1 second
Response Time	<30 Seconds (Diffusion limited)
Sample Method	Solid-state LED NDIR Diffusion

## Electrical and Mechanical Specifications

Measurement Output	UART or I <sup>2</sup> C
Supply Voltage	3.25V - 5.5V
Power Consumption (typ.)	<3.5mW @ 3.3V
Dimensions and Weight	31mm x 19.5mm x 8.7mm, 2.5g

## Operating Conditions

Operating Conditions - Temperature	0°C to 50°C
Operating Conditions - Humidity	0-95% RH, non-condensing
Storage Conditions - Temperature	-30°C to +70°C
Pressure Dependence	500mbar - 1500mbar
Sensor Lifetime	>15 years
Environmental Compliance	RoHS and REACH

Product Flyer- Document Version: 06/03/2020-001