

K310


PLATFORM CONTROL SYSTEM FOR BATTERY POWERED SCISSOR LIFT

Introduction

The K310 Platform Control System provides the reliability required in demanding applications such as Mobile Elevating Work Platforms; K310 is committed to the full control of DC battery powered self-propelled scissor lift. The key parts of the K310 Kit are the PCU500 (Platform Control Unit) and the ECU310 (Electronic Control Unit). The 2 units have been conceived as building block elements able to connect a variety of digital and analog machine interfaces such as joysticks, sensors, limit switches, LEDs, motor controller, pushbuttons, e-stop, alarms and control them through a CAN-bus system.



PCU500
Platform Control Unit



ECU310
Electronic Control Unit

Main Features

- Four push button switches with LED backlit indicators
- Direction control switches integrated in the joystick grip
- 7 segment displays on both PCU and CPU for diagnostic
- Emergency Stop Pushbutton
- Analog inputs 0-5V or 4-20mA configurable via software

Custom Modifications

- Custom overlay graphics
- Custom grip
- 30 functionally configurable Input/Output signals

SPECIFICATIONS

Electrical

	PCU500	ECU310
Supply Ratings	Nominal Voltage: 12V or 24V DC	
	Max. Voltage Range: 10V-30V	
	Max. output voltage: V supply DC	N/A
Other Electrical Characteristics	N/A	ESD: +/- 6KV Contact, +/-8KV Air Discharge per IEC 61000-4-2

Mechanical

	PCU500	ECU310
Operating temperature	-40 °C to 85 °C	
Protection Level	IP65 (after installed)	IP25
Life	Joystick > 5 million cycles Pushbuttons > 1million cycles	N/A

PCU500 Platform Control Unit

Connector: 6 Pin, SIBAS HQ-005-M; Pin Current Rating 7.5Amps

Pin 1	Ground
Pin 2	Serial Data High
Pin 3	E-Stop Out (+24V out)
Pin 4	+24V in
Pin 5	Serial Data Low
Pin 6	Unused

ECU310 Electronic Control Unit


Connector: 36 Pin, AMP 344108-1; Pin Current Rating 10Amps; gold plating on mating area of pins

Pin	I/O Type	Pin	I/O Type	Pin	I/O Type
1A	0-24V Digital Input	1B	Serial Data High	1C	Serial Data Low
2A	2.5A/24V Digital Output	2B	0-24V Digital Input	2C	Power Input
3A	2.5A/24V Digital Output	3B	Ground	3C	0-5V or 4-20mA Analog Input
4A	Power Input	4B	4-20mA Analog Input	4C	0-5V Analog Output
5A	Power Input	5B	Digital Input w/ 2.2K pull up	5C	Digital Input w/ 2.2K pull up
6A	2.5A/24V Digital Output	6B	2.5A/24V Digital Output	6C	2.5A/24V Digital Output
7A	2.5A/24V Digital Output	7B	2.5A/24V Digital Output	7C	2.5A/24V Digital Output
8A	2.5A/24V Digital Output	8B	2.5A/24V Digital Output	8C	2.5A/24V Digital Output
9A	0-5V Analog Output	9B	Alarm OC Input	9C	2.5A/24V Digital Output
10A	0-24V Digital Input	10B	0-24V Digital Input	10C	0-24V Digital Input
11A	0-5V or 4-20mA Analog Input	11B	0-24V Digital Input	11C	0-24V Digital Input
12A	0-24V Digital Input	12B	0-24V Digital Input	12C	0-24V Digital Input


DIMENSIONS

All dimensions are in inches [millimeters]

PCU500 Platform Control Unit



ECU310 Electronic Control Unit





Part Number	Product	Description
K310-VR1 ^(A)	K310	Platform Control Kit for DC vehicle

^(A) **K310 Kit includes:**

Part Number	Product	Description
P500-VR1	PCU500	Platform Control Unit
E310-VR1	ECU310	Electronic Control Unit
8C40002CC0005-01	MC300	Accessory - Motor Controller 24/36V 275Amp

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

CONTACT US

INDUSTRIAL SOLUTIONS DIVISION

Americas
+1 (800) 350 2727
sensors.deltatech@sensata.com
Europe, Middle East & Africa
+359 (2) 809 1826
ost-info.eu@sensata.com
Asia Pacific
sales.isasia@list.sensata.com
China +86 (21) 2306 1500
Japan +81 (45) 277 7117
Korea +82 (31) 601 2004
India +91 (80) 67920890
Rest of Asia +886 (2) 27602006
ext 2808